

Sentinel HL



| SuperPro Configuration Keys | Pro | Max | Max | Net |
|---------------------------------------|---|---|---|---|
| Form Factor | Mini | Mini | Micro | Mini |
| Key Type Configuration | SuperPro | SuperPro XM | SuperPro XM | SuperPro Net |
| Aes 128-Bit Encryption | √ | √ | √ | √ |
| Memory | 64 cells | 256 cells | 256 cells | 64 cells |
| Write Cycles (EEPROM / Flash) | At Least 1,000,000 | At Least 1,000,000 | At Least 1,000,000 | At Least 1,000,000 |
| Data Retention | At Least 10 Years | At Least 10 Years | At Least 10 Years | At Least 10 Years |
| Physical Specifications | | | | |
| Default Color | Purple | Green | Green | Red |
| Plastic Case Material | Polycarbonate | Polycarbonate | Polycarbonate | Polycarbonate |
| Operating Temperature | -25 °C to 85 °C -13 °F to 185 °F | -25 °C to 85 °C -13 °F to 185 °F | -25 °C to 85 °C -13 °F to 185 °F | -25 °C to 85 °C -13 °F to 185 °F |
| Humidity Rating | 0-95% | 0-95% | 0-95% | 0-95% |
| Power Consumption - operating/standby | 50mA / < 0.5 mA | 50mA / < 0.5 mA | 50mA / < 0.5 mA | 50mA / < 0.5 mA |
| Dimensions L x W x H (in mm) | 40.5 x 16 x 8 | 40.5 x 16 x 8 | 18 x 12.2 x 4.5 | 40.5 x 16 x 8 |
| Weight (in grams) | 5.63 | 5.63 | 1.64 | 5.63 |
| Certification | | | | |
| Safety Certifications | IEC 62368-1, EN 62368-1, UL 62368-1, CAN/CSA-C22.2, NO.62368-1 A, AS/NZS 60950.1 | IEC 62368-1, EN 62368-1, UL 62368-1, CAN/CSA-C22.2, NO.62368-1 A, AS/NZS 60950.1 | IEC 62368-1, EN 62368-1, UL 62368-1, CAN/CSA-C22.2, NO.62368-1 A, AS/NZS 60950.1 | IEC 62368-1, EN 62368-1, UL 62368-1, CAN/CSA-C22.2, NO.62368-1 A, AS/NZS 60950.1 |
| Certification / Compliance | RoHS, WEEE, REACH | RoHS, WEEE, REACH | RoHS, WEEE, REACH | RoHS, WEEE, REACH |
| EMC Certifications | CE, FCC, VCCI | CE, FCC, VCCI | CE, FCC, VCCI | CE, FCC, VCCI |