



Sentinel HL

Driverless Configuration Keys	Basic	Pro	Max	Time
Form Factor	Mini	Mini	Mini	Midi
Security And Cryptographic Algorithms				
Unique 32-Bit ID		✓	✓	✓
AES 128-Bit Encryption	✓	✓	✓	✓
64,000 Encryption Keys	1	✓	✓	✓
On Chip Execution (AppOnChip-32bit & 64bit Win)	✓*	✓*	✓	✓
Licensing Models Support				
Perpetual	✓	✓	✓	✓
Feature-Based		✓	✓	✓
Pay-Per-Use		✓	✓	✓
Network Concurrency		✓*	✓*	✓*
Time-Based		✓*	✓	✓
Custom		✓	✓	✓
Clock				
Real Time Clock				✓
V-Clock		✓*	✓	✓
Battery Life Warranty				4-Years
Real Time Clock Accuracy (at 25° ± 5° C)				≤ 12.8 minutes/year
Memory				
Protected Read / Write Memory		112 Bytes	4KB	4KB
Read Only Memory (ROM)		112 Bytes	2KB	2KB
Dynamic Memory			390KB	390KB
Data Retention		At Least 10 Years	At Least 10 Years	At Least 10 Years
Write Cycles (EEPROM / Flash)		At Least 1,000,000	At Least 1,000,000	At Least 1,000,000
Max. licensable modules (Features, depending on license complexity)		11-39	3484-24386	3484-24386
Flash (Read / Write) per second				
Flash Memory				
Physical Specifications				
Default Color	Blue	Purple	Green	Black
Plastic Case Material	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
Operating Temperature***	-25°C to 85°C -13°F to 185°F	-25°C to 85°C -13°F to 185°F	-25°C to 85°C -13°F to 185°F	-20°C to 60°C -4°F to 140°F
Humidity Rating	0-95%	0-95%	0-95%	0-95%
Power Consumption - operating / standby	50mA / < 0.5 mA	50mA / < 0.5 mA	50mA / < 0.5 mA	50mA / < 0.5 mA
Dimensions L x W x H (in mm)	40.5 x 16 x 8	40.5 x 16 x 8	40.5 x 16 x 8	52 x 16 x 8
Weight (in grams)	5.63	5.63	5.63	7.36
Certification				
Safety Certifications	IEC 62368-1, EN 62368-1, UL 62368-1, CAN/CSA-C22.2 NO.62368-1 A, AS/NZS 60950.1	IEC 62368-1, EN 60950-1, UL 62368-1, CAN/CSA-C22.2 NO.62368-1 A, AS/NZS 60950.1	IEC 62368-1, EN 60950-1, UL 62368-1, CAN/CSA-C22.2 NO.62368-1 A, AS/NZS 60950.1	IEC 62368-1, EN 60950-1, UL 62368-1, CAN/CSA-C22.2 NO.62368-1 A, AS/NZS 60950.1
Certification / Compliance	RoHS, WEEE, REACH	RoHS, WEEE, REACH	RoHS, WEEE, REACH	RoHS, WEEE, REACH
EMC Certifications	CE, FCC, VCCI	CE, FCC, VCCI	CE, FCC, VCCI	CE, FCC, VCCI



Driverless Configuration Keys	Max	Drive microSD**	Max	Max
Form Factor	Board	Midi	Micro	Chip
Security And Cryptographic Algorithms				
Unique 32-Bit ID	✓	✓	✓	✓
AES 128-Bit Encryption	✓	✓	✓	✓
64,000 Encryption Keys	✓	✓	✓	✓
On Chip Execution (AppOnChip-32bit & 64bit Win)	✓	✓	✓	✓
Licensing Models Support				
Perpetual	✓	✓	✓	✓
Feature-Based	✓	✓	✓	✓
Pay-Per-Use	✓	✓	✓	✓
Network Concurrency	✓*	✓*	✓*	✓*
Time-Based	✓	✓	✓	✓
Custom	✓	✓	✓	✓
Clock				
Real Time Clock				✓
V-Clock	✓	✓	✓	✓
Battery Life Warranty				
Real Time Clock Accuracy (at 25° ± 5° C)				
Memory				
Protected Read / Write Memory	4KB	4KB	4KB	4KB
Read Only Memory (ROM)	2KB	2KB	2KB	2KB
Dynamic Memory	25KB	25KB	390KB	25KB
Data Retention	At Least 10 Years	At least 10 Years	At least 10 years	At least 10 years
Write Cycles (EEPROM / Flash)	At Least 1,000,000	At least 1,000,000	At least 1,000,000	At least 1,000,000
Max. licensable modules (Features, depending on license complexity)	240-2160	240-2160	3484-24386	240-2160
Flash (Read / Write) per second			*Depends on microSD card	
Flash Memory			Support microSD card up to 64GB	
Physical Specifications				
Default Color	Black	Green	Green	Black
Plastic Case Material		Polycarbonate		
Operating Temperature***	-25°C to 85°C -13°F to 185°F	0°C to 60°C 32°F to 140°F	-40°C to 85°C -40°F to 185°F	-25°C to 85°C -13°F to 185°F
Humidity Rating	0-95%	0 - 95%	0-95%	0-95%
Power Consumption - operating / standby	20mA / < 0.5 mA	200mA max	50mA/<0.5mA	20mA/<0.5mA
Dimensions L x W x H (in mm)	15.2x8x12.4	52x16x8	18x12.2x4.5	8.2x5.3x2.1
Weight (in grams)	1.23	6.98	1.64	NA
Certification				
Safety Certifications	IEC 62368-1, EN 62368-1, UL 62368-1, CAN/CSA-C22.2 NO.62368-1 A, AS/NZS 60950.1	IEC 62368-1, EN 62368-1, UL 62368-1, AS/NZS 60950.1	IEC 62368-1, EN 62368-1, UL 62368-1, CAN/CSA-C22.2 NO.62368-1 A, AS/NZS 60950.1	
Certification / Compliance	RoHS, WEEE, REACH	RoHS, WEEE, REACH	RoHS, WEEE, REACH	RoHS, REACH
EMC Certifications	CE, FCC, VCCI	CE, FCC, VCCI	CE, FCC, VCCI	

* Requires a paid upgrade. ** Supported only with Sentinel LDK 7.4 and later.

*** The host USB port which powers the hardware key should be compliant with LPS (Limited Power Source) requirement in IEC 62368-1 clause 2.5. The operating temperature of the hardware keys is up to 85°C, and to avoid scalding, do not touch the keys with hands directly when the environment temperature is higher than 50°C.

> cpl.thalesgroup.com/software-monetization <



Contact us - For office locations and contact information, please visit cpl.thalesgroup.com/software-monetization/contact-us