

Thales CN9120 Network Encryptor

100 Gbps high speed data in motion encryption



Delivering 100,000,000,000 bits per second of high-assurance data encryption, the Thales CN9120 Network Encryptor provides data security (100 Gbps) and high speed network performance with ultra-low latency (<2 μ S). Safeguard data in motion with high speed encryption proven to meet network performance demands for real-time low latency and near-zero overhead, ensuring security without compromise for big, or even data transmitted over networks across data centers and the cloud.

With the ever-increasing growth in data volumes and demand for higher bandwidth services, the CN9120 is the ideal solution for organizations that are racing ahead at full speed, at 100 Gbps. The CN9120 is a high-assurance encryptor designed to provide 100 Gbps highly secure, full line rate encryption of all voice, video and data communications moving across dark fibre, and metro or wide area and Carrier Ethernet networks (MAN or WAN). Ideally suited to encrypt provider networks, data center interconnect and disaster recovery links, it supports all network topologies including multi-point to multi-point environments.

Performance



Why CN9120 Encryptors?

Trusted Security

- True end-to-end, authenticated encryption
- State-of-the-art automatic zero-touch key management
- Designed for FIPS 140-2 L3, Common Criteria, NATO, UC APL
- Preferred by market leading commercial and government enterprises in over 35 countries

Maximum Network Performance

- Microsecond latency (<2 μ S)
- Near-zero overhead
- Self-Healing capabilities for maximum up time

Scalable and Simple

- Point to Point, Hub and Spoke and Full Mesh
- Fully auditable alarm and event logs from 3rd party management tools
- Field serviceable with hot swappable fans

The CN9120 is an ultra-high-performance encryptor, operating in full-duplex mode at 100 Gbps line rate speed. Using Field Programmable Gate Array (FPGA) technology, the CN9120's architecture enables real-time data processing and high throughput. This ensures consistent low latency across all packet sizes for optimal performance. Throughput is maximized in a zero protocol overhead mode. A 1U unit, it operates with minimal power and rack space consumption.

Scalability

Standards compliant, the CN9120 is fully interoperable with industry standard network equipment from leading vendors. The 'Bump in the Wire' design provides a vendor-agnostic and drop in the network approach to 100 Gbps encryption. The CN9120 is easy to install and highly cost-effective. "Set and forget" simplicity, and application and protocol transparency are underlying design themes, ensuring easy implementation, operation and management, and minimal resource requirements. Devices can be field upgraded on site with ease, for maintenance, feature enhancements and security updates.

Certified Security and Crypto-Agility

Designed for security conscious organizations, the tamper resistant CN9120 is in process for Common Criteria EAL4+ and FIPS 140-2 Level 3 certifications and supports automatic zero-touch key management.

Enabling crypto-agility, the CN9120's advanced security features include support for a wide range of elliptic curves (Safe Curves, Brainpool, NIST). Custom curves and custom entropy are a standard feature of the encryptors' software.

VLAN based encryption provides unique key pairs in hub and spoke environments to protect against misconfigured traffic.

State-of-the-Art Key Management

The CN9120 removes reliance on external key servers and provides a robust fault-tolerant security architecture and tamper-resistant chassis. Physical and virtual separation of duties ensures that only authorized users can access the keys. Encryption keys are generated and stored securely in hardware within the device's tamper-resistant enclosure, and any unauthorized attempts to physically extract the keys will result in device zeroization. The CN9120 supports hardware based random number generators and can use externally generated entropy for intrinsic key generation and distribution. For future-proofing, the encryptors support Quantum Key Distribution (Quantum Cryptography) and Quantum random number generation.

Next Gen High Speed Encryption

Crypto-Agility

Thales Network Encryptors are crypto-agile, meaning they support customizable encryption for a wide range of elliptic and custom curves support. The appliances also allow your own entropy capabilities. The crypto-agile platform is future proof, allowing for responsive deployment of next-gen or custom algorithms. In response to the Quantum threat, Thales Network Encryptors already leverage Quantum Key Distribution (QKD) and Quantum Random Number Generation (QRNG) capabilities for future-proof data security.

Transport Independent Mode

Transforming the network encryption market, Thales Network Encryptors are the first to offer Transport Independent Mode (TIM) - network layer independent (Layer 2, Layer 3, and Layer 4) and protocol agnostic data in motion encryption. By supporting Layer 3, Thales Network Encryptors offer network operators more configuration options using TCP/IP routing for securing critical data.

CN9120 Encryptor At-A-Glance

Model	CN9120
Protocol and Connectivity	
Maximum Speed	100 Gbps
Support for Jumbo frames	Yes
Protocol and application transparent	Yes
Encrypts Unicast, Multicast and Broadcast traffic	Yes
Automatic network discovery and connection establishment	Yes
Network interfaces	QSFP28
Security	
Tamper resistant and evident enclosure, anti-probing barriers	Yes
Flexible encryption policy engine	Yes
Automatic key management	Yes
Encryption and Policy	
AES 256 bit keys	Yes
Encryption mode	CTR
Policy based on MAC address or VLAN ID	Yes
Self-healing key management in the event of network outages	Yes
Certifications: In progress	
Designed for Common Criteria, FIPS, NATO, UC APL*	Yes

Performance	
Low overhead full duplex line-rate encryption	Yes
FPGA based architecture	Yes
Latency (microseconds per encryptor)	<2 μS
Management	
Front panel access for all interfaces	Yes
Centralized configuration and management using SMC/CM7 and SNMPv3	Yes
Support for external (X.509v3) CAs	Yes
Remote management using SNMPv3 (in-band and out-of-band)	Yes
NTP (time server) support	Yes
CRL and OCSP (certificate) server support	Yes
Maintainability/Interoperability	
In-field firmware upgrades	Yes
Dual hot-swappable AC power supplies	Yes
User replaceable fans and batteries—dual redundancy	Yes
Interoperable with all CN Series Encryptors	Yes

*In process

All specifications are accurate as at the time of publishing and are subject to change without notice.

Specifications

Physical security

- Active/Passive tamper detection and key erasure

Cryptography

- AES 256 bit key X.509 certificates (CTR mode)
- Hardware based random number generator

Device management

- Dedicated management interface (out-of-band)
- Encrypted interface (in-band)
- SNMPv3 remote management
- IPv4 & IPv6 capable
- Supports Syslog, NTP
- Alarm, event & audit logs
- Command line serial interface
- TACAS+ support
- RADIUS support

Installation

- Size: 435mm, 43mm, 480mm / 17.1", 1.7", 18.9"
- 1U 19" rack mountable
- Weight: 8kg / 17.6 lbs

Power Requirements

- AC Input: 100 to 240V AC; 1.5A; 50/60Hz
- Power Consumption: 80W typical

Regulatory Safety

- UL Listed (in progress)
- EMC (Emission and Immunity)
- FCC 47 CFR Part 15 (USA)
- EN 55024 (CE), 55022 (CE)
- EN 60950-1 (CE), 61000-3-2 (CE), 61000-3-3 (CE)
- IEC 60950-1 Second Edition
- ICES-003 (Canada)
- AS/NZS 60950-1, CISPR 22 (RCM)

Environmental

- RoHS Compliant
- Max operating temperature: 40°C / 104°F
- 0 to 80% RH at 40°C / 104°F operating

About Thales

The people you rely on to protect your privacy rely on Thales to protect their data. When it comes to data security, organizations are faced with an increasing number of decisive moments. Whether the moment is building an encryption strategy, moving to the cloud, or meeting compliance mandates, you can rely on Thales to secure your digital transformation.

Decisive technology for decisive moments.

> cpl.thalesgroup.com <    

Americas – Arboretum Plaza II, 9442 Capital of Texas Highway North, Suite 100, Austin, TX 78759 USA • Tel: +1 888 343 5773 or +1 512 257 3900 • Fax: +1 954 888 6211 • E-mail: sales@thalessec.com
Asia Pacific – Thales Transport & Security (HK) Lt, Unit 4101-3, 41/F, Sunlight Tower, 248 Queen's Road East, Wanchai, Hong Kong • Tel: +852 2815 8633 • Fax: +852 2815 8141 • E-mail: apacsales.cpl@thalesgroup.com
Europe, Middle East, Africa – 350 Longwater Ave, Green Park, Reading, Berkshire, UK RG2 6GF • Tel: +44 (0)1844 201800 • Fax: +44 (0)1844 208550 • E-mail: emea.sales@thales-esecurity.com