

# Thales **CN7108** Network Encryptor

Engineered for  
Extreme Environments:  
Ruggedized Encryption  
for the Tactical Edge

The Thales CN7108 Network Encryptor (CN7108) extends the Thales High Speed Encryptor (HSE) network encryption portfolio to new frontiers, to tactical, industrial, IoT, and remote edge deployments. Purpose-built on ruggedized industrial-grade hardware, the CN7108 delivers FIPS 140-3 certified, quantum-resistant, crypto-agile data in motion encryption at up to 1 Gbps. With MIL-STD-810G compliance, extended temperature resilience, and optimization of footprint, power and cost, it ensures trusted security for mission-critical operations in the harshest environments.



## Certified Security and Crypto-Agility

The CN7108 delivers **FIPS 140-3 Level 1 certified encryption** with AES-128/256 keys, X.509 RSA/ECC authentication, and authenticated GCM/CTR modes. It is **quantum-ready**, supporting NIST PQC standards and hybrid cryptography, and enables sovereign or custom ciphers through a Cryptographic SDK (CSDK).

## Maximum Network Performance

With up to 1 Gbps encrypted throughput, the CN7108 ensures secure, real-time protection for data in motion. Its **Transport Independent Mode (TIM)** delivers tunnel-free, low-overhead encryption at Layer 2, 3, or 4 across Ethernet, MPLS, satellite, cellular, and Internet transport.

## Scalability and Flexibility

**Compact and ruggedized**, the CN7108 measures 132.8 × 100 × 34.8 mm (5.2 × 3.9 × 1.4 in) and weighs ~420 g (0.93 lbs). Its tamper-evident enclosure ensures physical security in the field. It operates across -40 °C to +85 °C (-40 °F to +185 °F), is MIL-STD-810G compliant for shock and vibration, and features fanless, solid-state construction for silent, reliable operation. It supports point-to-point, hub-and-spoke, and full mesh topologies, and is optimized for deployment in size, weight, and power-constrained environments. It is fully interoperable with all Thales High Speed Encryptors for seamless integration into existing networks.

## Why CN7108 Encryptors?

- FIPS 140-3 certified, quantum-ready encryption
- Ruggedized industrial-grade hardware, MIL-STD-810G compliant
- Tamper-evident enclosure for enhanced physical security
- High assurance design for maximum uptime in harsh environments
- Operates from -40 °C to +85 °C (-40 °F to +185 °F)
- Optimized for remote edge, IoT, and tactical use cases
- Automated zero-touch key management
- Fully interoperable with the Thales High Speed Encryptor portfolio

## Advanced Encryption and Key Management

The CN7108 employs **X.509 certificates with RSA/ECDH exchanges** in Ethernet encryption modes. In Transport Independent Mode (TIM) it uses **NIST-validated key generation ensuring robust, quantum-safe data protection with perfect forward secrecy**. It also integrates with external Key Servers, including Thales CipherTrust Data Security Platform.

LINE & VLAN modes allow encryption across any Ethernet service for unicast, multicast, and broadcast traffic, with unique encryption keys to ensure cryptographic isolation per VLAN.

## User-Friendly Management

With intuitive, **centralized management**, the CN7108, like the rest of the Thales High Speed Encryptor product suite, offers set-and-forget simplicity with protocol and network transparency. The CN7108 supports Syslog, NTP, SNMPv3, alarm and event logging, and secure management channels. Firmware upgrades are enabled through USB, and local configuration is available via serial console with SSH.

## CN7108 At-a-Glance

<b>Performance</b>	Up to 1 Gbps encrypted throughput
<b>Crypto</b>	AES-128/256, RSA/ECC certificates, GCM/CTR, PQC support, sovereign/custom ciphers via CSDK
<b>Interfaces</b>	2 × Gigabit Ethernet traffic, 2 × Gigabit management, USB, serial console
<b>Management</b>	CM7, SMC, Syslog, SNMPv3, NTP
<b>Environmental</b>	−40 °C to +85 °C (−40 °F to +185 °F), MIL-STD-810G shock & vibration, fanless
<b>Form Factor</b>	132.8 × 100 × 34.8 mm (5.2 × 3.9 × 1.4 in), ~420 g (0.93 lbs)
<b>Power</b>	9–42 V DC input, optional PoE
<b>Certifications</b>	FIPS 140-3 Level 1, MIL-STD-810G

## Specifications

### Performance

- Throughput: 1 Gbps full duplex line-rate encryption

### Cryptographic Security

- AES-128/256 encryption, GCM/CTR modes
- X.509 RSA/ECC certificates
- FIPS 140-3 Level 1 certified crypto module
- Quantum-ready (NIST PQC standards)
- Custom ciphers with CSDK

### Interfaces

- 2 × RJ45 Gigabit Ethernet (Local/Network)
- 2 × RJ45 Gigabit Ethernet (Management)
- USB ports (firmware upgrade, debug)
- Serial console with SSH

### Environmental

- Operating: −40 °C to +85 °C (−40 °F to +185 °F)
- Humidity: 5% – 95% non-condensing
- MIL-STD-810G shock & vibration
- Fanless, solid-state housing

### Physical

- Dimensions: 132.8 × 100 × 34.8 mm (5.2 × 3.9 × 1.4 in)
- Weight: ~420 g (0.93 lbs)
- Tamper-evident enclosure for enhanced physical security

### Power

- Input: 9–42 V DC, up to 3.33 A (30–155 W depending on load)
- Optional PoE

### Management

- Centralized management - CM7 and SMC support
- SNMPv3, Syslog, NTP, audit/event logging
- Alarm and event notifications

### SWaP

- Optimized for size, weight and power.

### Regulatory Safety and Compliance

- CE (Conformité Européenne)
- FCC Part 15 (USA)
- ICES-003 (Canada)
- EMC (emission and immunity)
- IEC/EN 62368-1 (safety of information technology equipment)
- RoHS, WEEE, and REACH environmental compliance

## About Thales

Thales is a global leader in cybersecurity, helping the most trusted companies and organizations around the world protect critical applications, sensitive data, and identities anywhere at scale. Through our innovative services and integrated platforms, Thales helps customers achieve better visibility of risks, defend against cyber threats, close compliance gaps, and deliver trusted digital experiences for billions of consumers every day.