

RSA Event Source Configuration Guide

SafeNet HSM

Last Modified: Tuesday, August 12, 2014

Event Source (Device) Product Information	
Vendor	SafeNet
Event Source (Device)	Hardware Security Module
Supported Versions	6.2.0
RSA Product Information	
Supported Version	RSA enVision 4.0 and 4.1 Security Analytics 10.0 and later
Event Source (Device) Type	safenethsm, 321
Collection Method	Syslog
Event Source (Device) Class.Subclass	Security.Access Control
Content 2.0 Table	Firewall

This document contains the following information for the SafeNet HSM event source:

- [Configuration Instructions](#)
- [Release Notes 20140812-120845](#)

SafeNet HSM Configuration Instructions

Configure SafeNet Hardware Security Module

To configure SafeNet HSM:

1. Log on to the SafeNet DataSecure Management Console.
2. In the Device tab, select **Log Configuration > Rotation & syslog**.
3. Click the **Edit** button in the **Syslog Settings** section.
4. For the **System** and **Audit** rows, enter the IP address for the enVision appliance in the **Syslog Server #1 IP** field.
5. You can accept the remaining default values, or enter other values as needed.
6. Click **Save** to save your changes.

SafeNet HSM Release Notes (20140812-120845)

What's New in This Release

RSA added support for SafeNet HSM.